

# A Lower Bound for the Sturm-Liouville Eigenvalue Problem on a Quantum Computer

Arvid J. Bessen<sup>a</sup>

<sup>a</sup>bessen@cs.columbia.edu  
Department of Computer Science  
Columbia University

We study the complexity of approximating the lowest eigenvalue of a Sturm-Liouville differential equation on a quantum computer. This general problem includes the special case of computing the ground state energy of a quantum system for a given potential.

Recently Papageorgiou and Woźniakowski proved that quantum computers could achieve exponential speedups compared to classical computers for certain potentials. Let  $\mathbb{L}_q$  be the differential operator for the Sturm-Liouville problem. Papageorgiou's and Woźniakowski's method uses the (discretized) unitary propagator  $\exp(i\mathbb{L}_q)$  as a query. They showed that if the operator  $\exp(ip\mathbb{L}_q)$  (a "power query") is computable in cost comparable to  $\exp(i\mathbb{L}_q)$  for any integer  $p$ , one can solve the Sturm-Liouville problem with  $\mathcal{O}(\log \epsilon^{-1})$  power queries.

In this paper we will prove a matching lower bound of  $\Omega(\log \epsilon^{-1})$  power queries, therefore showing that  $\Theta(\log \epsilon^{-1})$  power queries are sufficient and necessary. Our proof is based on a frequency analysis technique, which examines the probability distribution of the final state of a quantum algorithm and the dependence of its Fourier transform on the input.