

# Tutorial 6

14.11

1. Reachability for VASS with negative semantic belongs to NP.

Brief theoretical introduction (hint):

Linear programming (LP)

a minimization / maximization problem for a linear function of  $n$  arguments:  $x_1, x_2, \dots, x_n$ , where the arguments have to satisfy some conditions (linear equations or inequalities using  $x_i$ s)

Example:

$$\max \quad x_1 + 2x_2$$

$$\text{s.t.} \quad x_2 \leq x_1 + 2$$

$$2x_1 + x_2 \leq 4$$



solvable in  
polynomial  
time

Integer programming (IP)

↑ for each  $i \in \{1, 2, \dots, n\}$  we add a condition  $x_i \in \mathbb{Z}$   
this problem is NP-complete

Given: VASS  $(Q, T)$

Question:  $(p, u) \dashrightarrow^* (q, v)$  ?

does there exist a run that can drop below zero

## Attempt 1

\* denote transition vectors by  $v_1, v_2, \dots, v_n$

\* solve a set of linear equations

$$\begin{bmatrix} \vdots & \vdots & \vdots & \vdots \\ v_1 & v_2 & \dots & v_n \\ \vdots & \vdots & \vdots & \vdots \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \\ \vdots \\ x_n \end{bmatrix} = v - u$$

where  $x_i$  is the number of times transition  $t_i$  is to be fired (used)

Problem: we can obtain  $x_i \notin \mathbb{Z}$  and  $x_i < 0$

## Attempt 2

and the goal of IP:  $\min \sum_{i=1}^n x_i$

\* add conditions:  $x_i \in \mathbb{Z}$ ,  $x_i \geq 0$  for each  $i$

Problem: firing each transition  $t_i$   $x_i$  times


gives  $v - u$  but the transitions may

not form a run in VASS

### Attempt 3

- \* add Kirchoff's law conditions - for each state except  $q, q'$  the number of incoming transitions (sum of  $x_i$ ) equals the number of outgoing ones
- \* for  $q$  there is one more outgoing transition and for  $q'$  - one more incoming

Problem:  $x_i$  can describe a path from  $q$  to  $q'$  and a disjoint cycle...




## Attempt 4

- \* after obtaining  $x_i$ 's, define  $S = \{t_i \in T \mid x_i > 0\}$  and check whether each  $t_i \in S$  can be reached from  $q$  using transitions in  $S$
- \* the condition above ensures that we can create the run given  $x_i$ 's (go from  $q$  using any available transition until reaching  $q'$  with the last transition incoming to  $q'$ ; then, if we still have some spare transitions, we can create some cycles and glue them to the run  $q \rightarrow^* q'$ )
- \* it seems like it should be enough for  $S$  to be connected in order to create such a run

Problem: solution to our LP program may not satisfy the condition from attempt 4, but there can be some other run that does

received solution,  
unable to create  
a run based on it



another feasible  
solution that corresponds  
to a run but doesn't  
minimize the goal function

## Attempt 5 - final approach

- \* to ensure that every possible run is taken into account we can guess the transition set  $S'$  that we allow the use of and then solve IP with conditions

$$\forall i \in S' \quad x_i > 0$$

$$\forall i \in T \setminus S' \quad x_i = 0$$

2. Using the insights from the previous problem present a way to check condition  $\Theta_1$

$\Theta_1$ : for every  $m \geq 1$   $(q, v) \dashrightarrow^* (q', v')$   
using every transition  $\geq m$  times

- \* if there exists a run  $r'$  for some selected  $m' > 0$  using every transition  $t_i$   $x_i \geq m'$  times, then there also exists a run  $r''$  that uses each transition at least  $m'' = \max(x_i) + 1$  times (we use notation  $\# t_i \rightarrow y_i$  for  $r''$ )

- \* both  $r'$  and  $r''$  satisfy the Kirchoff's law, hence so does  $r'' - r'$  which uses each transition  $t_i$  at least  $y_i - x_i > 1$  times
- \* thus,  $r'' - r'$  is a cycle that has no side effect on a given configuration
- \* the solution idea:
  - define two sets of variables:  $x_1, x_2, \dots, x_n$  and  $\Delta_1, \Delta_2, \dots, \Delta_n$  such that both sets satisfy Kirchoff's law (first with a twist for  $q$  and  $q'$ )
  - $x_i > 0$  (for a subset of transitions - as discussed before), firing all  $t_i$ s  $x_i$  times results in  $v' - v$  change on the configuration
  - $\Delta_i > 0$  for all transitions and firing  $t_i$ s don't change the configuration

3. Prove that the following implication holds:

$\exists m$ . every configuration reachable from  $(q, v)$  has some coordinate  $< m$  ] (1)

$\Downarrow$

$\exists m$ . every run from  $(q, v)$ , on some coordinate, is always  $< m$  ] (2)


\* if (1) holds, we can set  $m$  to be the greatest integer appearing in the coverability tree (it might take a lot of time to find  $m$  but we can afford it; also, for VASSes we have to remember the state we are in)

\* now, we show that such an  $m$  satisfies (2)

\* first, assume that the VASS is 2-dimensional and assume that there exists a run  $r$  such that  $r$  goes through points  $(v_1, v_2)$  with  $v_1 \geq m$  and  $(u_1, u_2)$  with  $u_2 \geq m$

\* it means that we had to reach  $(p, (w, -))$  in the coverability tree  $\Rightarrow$  there exists a sequence  $\sigma$  of transitions that starts and ends in  $p$ , increases the first coordinate and doesn't change the second one

\* we can fire  $\sigma$  as many times as it is required to increase the first coordinate by  $\geq m$ , i.e., we extend  $r$  in such a way



\* it gives us a new run  $r'$  that instead of  $(u_1, u_2)$  reaches  $(u_1 + k, u_2)$  with  $k \geq m$


\* this configuration doesn't satisfy (1) - contradiction

\* for higher dimensions the reasoning is similar (the only problem: going from  $(w, x_1, \dots, x_d)$  to  $(w, w, y_1, \dots, y_d)$  might decrease first coordinate)

4. How to reduce coverability to reachability in general Petri nets?

First solution


from now on we assume that each initial net has  $r$  places



$(N, M_0)$ : can we cover  $M$ ?

$\Downarrow$   
 $(M_0, 0)$   
 $\Downarrow$   
 $(N', M'_0)$ : can we reach  
 $(0, 0, \dots, 0, 1)$ ?

Second solution



$(N, M_0)$ : can we cover  $M$ ?

$\Downarrow$   
 $(N', M_0)$ : can we reach  $M$ ?

5. Show reductions between the following problems:


1) reachability problem:  $M \in \mathbb{N}^r$ , is  $M$  reachable? (RP)

2) submarking reachability problem:  $\tilde{P}$  - subset of places,  $M_{\tilde{P}}$  - configuration over  $\tilde{P}$ , does there exist a reachable configuration  $M$  such that over the places of  $\tilde{P}$  it agrees with  $M_{\tilde{P}}$ ? (SRP)


3) zero reachability problem: is  $\mathbf{0}$  reachable? (ZRP)

4) single-place zero reachability problem: given a place  $p$ , does there exist a reachable configuration  $M$ , s.t.  $M(p) = 0$ ? (SPZRP)

The idea is to show the following reductions:



"Y is reducible to X"



$\rightarrow$  easy reduction


$\Rightarrow$  reduction to present

## ZRP $\Rightarrow$ SRP:

- \* given a net  $(N, M_0)$  and a submarking  $M_{\tilde{P}}$  over a subset  $\tilde{P} \subseteq P$ , is there a reachable configuration  $M$  that agrees with  $M_{\tilde{P}}$  over  $\tilde{P}$ ?  
 $\nwarrow (P, T, F)$
- \* we will answer this question by asking for zero configuration reachability in another net (obtained by modifying  $(N, M_0)$ )
- \* first, we add a "run" place  $p_0$  that contains one token and is connected with each transaction of the original net in both ways, i.e., for each  $t \in T$ :  $p_0 \in {}^*t$  and  $p_0 \in t^*$  (arc weight = 1)
- \* next, we add a transition  $\theta_0$  that takes one token from  $p_0$ , i.e., stops the normal run of  $N$  and puts a token on the "check" place  $\pi_0$  - this token allows the firing of new transitions  $\theta_1, \theta_2, \dots, \theta_r$
- \* for  $i \in P \setminus \tilde{P}$  transition  $\theta_i$  takes a token from  $p_i$

\* for  $i \in \tilde{P}$  transition  $\Theta_i$  takes one token from  $p_i$  and one from  $\pi_i$ ,  $\pi_i$  initially having  $M_{\tilde{P}}(p_i)$  tokens

\* finally, we have a transition  $\Theta'_0$  that takes one token from  $\pi_0$




\* it is obvious that zero configuration is reachable iff configuration  $M_{\tilde{P}}$  over  $\tilde{P}$  is reachable in  $N$

## SP2RP $\Rightarrow$ ZRP:

- \* now, we can use the blackbox for answering single-place zero reachability problem and have to answer the zero reachability problem in  $N$
- \* the idea is to have a new place  $\Pi$  s.t. at all times  $\Pi$  contains as many tokens as there are in all places of  $N$ , i.e., at every configuration  $M$  in the new net  $N'$ : 
$$M(\Pi) = \sum_{i=1}^r M(p_i)$$
- \* to obtain it, we connect  $\Pi$  with all transitions of  $N$  with incoming and outgoing arcs - the weight of incoming arc is the sum of incoming arcs' weights in  $N$  and analogously for outgoing
- \* initially,  $\Pi$  contains the total number of tokens in configuration  $M_0$  for  $N$
- \* obviously,  $t_j \in T$  is fireable in  $N$  iff  $t_j$  is fireable in  $N'$
- \* answer for ZRP in  $N =$  answer for SP2RP in  $N'$

\* obtaining  $N'$  from  $N$  - example



Source of the net modification figures:

Michel Hack. Decidability Questions for Petri Nets

6. Structural unboundedness for general Petri nets belongs to NP.

homework (not obligatory)